

77) Journal of Mining Science

Volume 55, Issue 1, 1 January 2019, Pages 66-76

Backfilling Mixture Preparation Using Milled Granulated Blast-Furnace Slag(Article)

Krupnik, L.A.a, Shaposhnik, Y.N.b, Shaposhnik, S.N.c, Nurshaiykova, G.T.c [View Correspondence \(jump link\)](#)

aSatpaev Kazakh National Research Technical University, Almaty, 50013, Kazakhstan

bChinakal Institute of Mining, Siberian Branch, Russian Academy of Sciences, Novosibirsk, 630091, Russian Federation

cSerikbaev East Kazakhstan State Technical University, Ust-Kamenogorsk, 070000, Kazakhstan

Краткое описание [Просмотр пристатейных ссылок \(23\)](#)

Backfilling mixture preparation technology using a cement-slag binder is developed for the Artem'evsky mine. It is shown that backfill with granulated blast-furnace slag reaches project strength at its fineness 80% of content milled down to -80 urn size. The authors analyze influence of milling fineness of granulated blast-furnace slag from different manufacturers on strength and rheological properties of backfill. The economic analysis of cost of binder in formation of load-bearing layer of backfill prepared using fly ash and milled granulated blast-furnace slag is performed. © 2019, Pleiades Publishing, Ltd.